

OfficePower[™] 1250AVR

Automatic Voltage Regulator



PRODUCT FEATURES:

- Automatic Voltage Regulator ensures clean, consistent and computer-safe voltage level
- Battery Run-times from 40 to 100 minutes
- **Dual 9AH batteries for longer run-time**
- All outlets surge-protected at 1500 joules
- Internet-ready with two line phone/ fax/modem surge protection
- \$400,000 Connected Equipment Warranty











PowerPanelPlus Automatic Shutdown Software

- Saves open files, closes applications and shuts down your computer when a power outage occurs.
- Monitors input voltage, output voltage, battery capacity, load and unit temperature.
- Allows for user-defined scheduled shutdown and startup of computer system.

OfficePower 1250AVR Automatic Voltage Regulator


High Performance Power Protection with Automatic Voltage Regulation

CyberPower Systems' 1250AVR is an ideal unit for high-end computer systems or users who need extended run-times. The dual 9AH batteries provide ample run-time for today's power-hungry processors.

The AVR feature ensures that your sensitive electronic equipment receives only clean, consistent, regulated power, reducing system "lock-ups". CyberPower backs this unit with an impressive \$400,000 connected equipment guarantee. The 1250AVR sets the standard for quality, reliability and performance at a realistic price.

What is AVR?

Automatic Voltage Regulators increase low or decrease high voltage to a computer safe 110/120 volts. The 1250AVR automatically provides battery backup power if the line voltage drops below 85 volts or exceeds 150 volts.







- 1 Power On Indicator
- 2 Electrical Wiring Fault Indicator
- 3 AVR Indicator
- 4 Using Battery Indicator
- 5 Check Battery Indicator
- 6 Power Switch
- 7 All Outlets Designed for AC Adapters
- 8 Two (2) Line Phone/Fax/Modem Communication Protection Ports
- 9 Serial Port to PC
- 10 Full-time Surge Protection Outlets
- 11 Circuit Breaker
- 12 Battery Power Supplied Outlets

TECHNICAL SPECIFICATIONS

| Model | CPS1250AVR |
|-------------------------------|---|
| VA Rating | 1250VA |
| Watts | 670W |
| Input Voltage on Utility | 85V to150V |
| Frequency on Utility | 57Hz to 63 Hz |
| Output Voltage on Battery | 120V +/- 5% |
| Frequency on Battery | 60Hz |
| Surge Energy Capacity | 1500 Joules |
| Maximum Surge Current | 36,000 Amps |
| Overload Protection | Internal circuitry limiting. On-line circuit breaker |
| Battery Run-time | 40 to 100 mins. |
| Typical Battery Recharge Time | 8 hours |
| Total number of receptacles | 3 battery / surge, 3 full-time surge-only |
| Visual Indicators | Power On/Off, Automatic Voltage Regulator, Using Battery, Site Wiring Fault |
| Audible Indicators | Battery on, Low battery, UPS overload |
| Warranty | Three Year Limited Warranty on UPS unit and battery |
| Conformance Approvals | UL 1778, cUL, FCC Doc Class B |
| Included Software | PowerPanelPlusTM Power Management Software |
| Connected Equip. Guarantee | \$400,000 |
| • | - |

PACKAGING SPECIFICATIONS

| Part Number | CPS1250AVR |
|--------------------------------|--------------------------|
| Sell Unit Dims. (L" x W" x H") | 15.87" x 9.25" x 9.12" |
| Sell Unit Net Weight | 30 LBS. |
| Master Carton Quantity | 2 UNITS |
| Master Dims. (L" x W" x H") | 19.25" x 16.875" x 9.75" |
| Master Weight | 60 LBS. |
| UPC Number | 6 49532 01250 3 |



5555 12th Ave. East, Suite 110, Shakopee, MN 55379 Phone: 877.297.6937 Fax: 952.403.0009